

COOKER AND APPLIANCE CONNECTION BOXES RUBBER SCHUKO® PLUGS AND CONNECTORS FOR FIXED CONNECTIONS



Cooker and appliance connection boxes

Whether flush-mounted or surface-mounted with simple or multiple connection boxes, Merten cooker and appliance connection boxes meet all professional requirements and guarantee a safe, reliable and robust connection, not least thanks to their shatter-proof covers.

Rubber SCHUKO® plugs and connectors

Indestructible Merten rubber SCHUKO® plugs and connectors can take a lot, both in day-to-day use in the workshop and on large-scale building sites. Merten has suitable plugs and connectors for every area and type of application.

Thanks to a modular assembly system, the snap collars, screwed joints and hinged lids are compatible with all plugs and connectors and can be easily replaced. All Merten rubber plugs and connectors bear the hammer symbol as well as all recognised quality marks. Guaranteed product quality you can rely on day after day.





Cooker and appliance connection boxes



Plugs and connectors

408 COOKER AND APPLIANCE CONNECTION BOXES

408 Cooker and appliance connection boxes

409 Cable junction boxes

410 RUBBER SCHUKO PLUGS AND CONNECTORS

410 Heavy-duty all-rubber plugs and connectors

411 All-rubber plugs and connectors

412 Rubber plugs and connectors

413 Export versions

413 Still in the range

414 SCHUKO PLUGS AND CONNECTORS

414 SCHUKO socket-outlets

414 SCHUKO plugs and sockets

417 PLUGS AND CONNECTORS

417 PERILEX plugs and connectors

418 HNA plugs and connectors

Cooker and appliance connection boxes



Cooker connection box, flush-mounted

Nominal cross-section 2.5 mm²


Particularly flat design. With shatter-proof lid and snap lock, removable terminal block with 5 double terminals.

IP20

Technical Information: Cooker sockets (⇒ p. 445)

Note: If using extension claws art. no. 533591, also fits size 70 flush-mounted boxes.

Version	Art. no.	PU	PG	Info
polar white	520427	5/60	6.1	



Cooker connection box, flush- and surface-mounted

Nominal cross-section 2.5 mm²

With shatter-proof lid and snap lock. Screw and claw fixing for size 60 and 70 flush-mounted boxes with removable claws.

Large, clear wiring compartment. Dowel fixing and cable entry from above also possible. Strain relief.

IP20

Technical Information: Cooker sockets (⇒ p. 445)

Version	Art. no.	PU	PG	Info
polar white	520619	5/40	6.1	



Cooker connection box, flush-mounted

Nominal cross-section 4 mm²

IP20

Contents: With plaster adjustment ring, insulating mounting box, protective cover for plaster.

Version	Art. no.	PU	PG	Info
white	520227	2/22	6	



Cooker connection box, flush-mounted, IP 21

Nominal cross-section 4 mm²

Terminal block with 5 double terminals. Gasket on the underside of the cover and on the cable outlet.

IP21

Version	Art. no.	PU	PG	Info
white	520327	2/22	6	



Cooker connection box, surface-mounted

Nominal cross-section 6 mm²

With 5-pole terminal block.

IP20

Version	Art. no.	PU	PG	Info
white	520827	5/30	6	



IP20

Three-section appliance connection box, flush- and surface-mounted

Nominal cross-section 2.5 mm²

2 shatter-proof lids with snap lock, 3 removable terminal blocks with 12 double terminals. Large, clearly visible wiring compartments. Screw and claw fixing for size 60 and size 70 flush-mounted boxes (brick walls, cavity walls and concrete), with removable spreading claws. Dowel fixing also possible.

Technical Information: Cooker sockets (⇒ p. 445)

Version	Art. no.	PU	PG	Info
polar white	521044	5/20	6	



IP20

Three-section appliance connection box, flush-mounted

Nominal cross-section 2.5 mm²

2 x 5 double terminals, removable, to connect electric storage heaters or 2 different electrical household appliances.

Version	Art. no.	PU	PG	Info
white	521427	5/10	6	



IP20

Three-section appliance connection box, flush-mounted, large terminal compartment

Nominal cross-section 2.5 mm²

3 x 5 double terminals, 3 separate connection chambers to connect electric storage heaters or to power 3 different electrical household appliances.

Version	Art. no.	PU	PG	Info
white	521927	1/12	6	



Terminal block

5-pole, for 2.5 mm²
 Double terminals with hole diameter 3.8 mm.
 Very versatile.

▣ **Accessories from:** Cooker connection box, art. no. 520427, 521044, 521427, 521927.

Version	Art. no.	PU	PG	Info
white	520900	10/480	6	

Cable junction boxes

- Cable junction boxes allow cables of different cross-sections, from 3 x 1.5 mm² to 5 x 6 mm², to be connected safely and quickly.



Cable junction box

5 x 2.5 mm², ø 27.5 mm

For fixed cabling. With strain relief.
 Certified in line with VDE 0606.

IP54

Version	Art. no.	PU	PG	Info
5 x 2.5 mm ² , grey	526129	10/200	7	



Cable junction box

5 x 6 mm², ø 34.5 mm

For fixed cabling. With strain relief.
 Certified in line with VDE 0606.

IP54

Version	Art. no.	PU	PG	Info
5 x 6 mm ² , grey	526229	10/100	7	

SCHUKO rubber plugs and connectors for wind and weather.

- According to the regulations regarding electrical power systems (VDE 0100 § 55e), the only connectors and plugs permissible on building sites are those that conform to DIN 49440 and 49441 and are approved "for harsh conditions". These plugs and connectors bear the hammer symbol.
- IP 44 splashwater protection is achieved in conjunction with a snap collar and hinged lid.
- Modular system for the extension of SCHUKO plugs and connectors with snap collar, hinged lid and screwed joint.
- Material: Natural rubber
- Uniform design
- Easy grip thanks to optimised shaping of the surface
- Simple and quick installation thanks to easily accessible screws
- The strain relief allows cables with different diameters to be used

Heavy-duty all-rubber plugs and connectors

- Extra large terminal compartment
- Rubber insert for use in extreme conditions
- Screws at the front for ultimate tensile strength
- Modular system for easy extension
- Smart design



Heavy-duty all-rubber SCHUKO plug

16 A, AC 250 V, DIN 49441

Splash-proof plug. Robust design. Bend protection sleeve with membrane seal. Shatter-proof, corrosion-resistant. For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.

Version	Art. no.	PU	PG	Info
black	123551	10/80	4	



Heavy-duty all-rubber SCHUKO connector

16 A, AC 250 V, DIN 49440

Robust design. Bend protection sleeve with membrane seal. Shatter-proof, corrosion-resistant. For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.

- ▣ **Accessories:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Info
black	173091	10/60	4	



Heavy-duty all-rubber SCHUKO connector with snap collar

16 A, AC 250 V, DIN 49440

Robust design. Bend protection sleeve with membrane seal. Shatter-proof, corrosion-resistant. For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.

- ▣ **Accessories:** Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Replacement part: Snap collar for SCHUKO connector, art. no. 174196.

Version	Art. no.	PU	PG	Info
black	173092	10/40	4	



Heavy-duty all-rubber SCHUKO connector with snap collar and hinged lid

16 A, AC 250 V, DIN 49440

Splash-proof connector. Robust design. Bend protection sleeve with membrane seal. Shatter-proof, corrosion-resistant.

For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.

- ▣ **Accessories:** Screwed joint, art. no. 535491.

Replacement part: Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097.

Version	Art. no.	PU	PG	Info
black	173051	10/60	4	



Heavy-duty all-rubber SCHUKO plugs and connectors

16 A, AC 250 V, DIN 49440/49441

Splash-proof, heavy-duty all-rubber plugs and connectors with snap collar, hinged lid and screwed joint. Robust design. Bend protection sleeve with membrane seal. Shatter-proof, corrosion-resistant. For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.

- ▣ **Replacement part:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Info
black/yellow	535593	1/12	4	



Screwed joint

For plugs and connectors with snap collars.

- ▣ **Accessories from:** SCHUKO plugs and connectors, art. no. 535451/93, 535593.

Version	Art. no.	PU	PG	Info
yellow	535491	1/80	4	



Snap collar for SCHUKO connector

▣ **Accessories from:** Rubber SCHUKO connector, art. no. 1740..., 1741... All-rubber SCHUKO connector, art. no. 1729... Heavy-duty all-rubber SCHUKO connector, art. no. 1730...

Version	Art. no.	PU	PG	Info
black	174196	10/120	4	



Replacement hinged lid for all-rubber SCHUKO connector

▣ **Accessories from:** All-rubber SCHUKO connector, art. no. 1729... Heavy-duty all-rubber SCHUKO connector, art. no. 1730...

Version	Art. no.	PU	PG	Info
black	173097	10/120	4	

All-rubber plugs and connectors

- Extra large terminal compartment
- Rubber insert for use in extreme conditions
- Screws at the front for ultimate tensile strength
- Modular system for easy extension
- Smart design



All-rubber SCHUKO plug

16 A, AC 250 V, DIN 49441

Splash-proof plug. Robust design, corrosion-resistant. Highly shatter-resistant. For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.



Version	Art. no.	PU	PG	Info
black	122051	10/80	4	



All-rubber SCHUKO connector

16 A, AC 250 V, DIN 49440

Robust design, corrosion-resistant. Highly shatter-resistant. For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.

▣ **Accessories:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Info
black	172991	10/80	4	



All-rubber SCHUKO connector with snap collar

16 A, AC 250 V, DIN 49440

Robust design, corrosion-resistant. Highly shatter-resistant. For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.

▣ **Accessories:** Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Replacement part: Snap collar for SCHUKO connector, art. no. 174196.

Version	Art. no.	PU	PG	Info
black	172951	10/80	4	



All-rubber SCHUKO connector with snap collar and hinged lid

16 A, AC 250 V, DIN 49440

Splash-proof connector. Robust design, corrosion-resistant. Highly shatter-resistant. For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.



▣ **Accessories:** Screwed joint, art. no. 535491.

Replacement part: Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097.

Version	Art. no.	PU	PG	Info
black	172993	10/40	4	



All-rubber SCHUKO plugs and connectors

16 A, AC 250 V, DIN 49440/49441

Splash-proof, all-rubber plugs and connectors with snap collar, hinged lid and screwed joint. Robust design, corrosion-resistant. Highly shatter-resistant. For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.



▣ **Replacement part:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Info
black/yellow	535493	1/12	4	



Screwed joint

For plugs and connectors with snap collars.

▣ **Accessories from:** SCHUKO plugs and connectors, art. no. 535451/93, 535593.

Version	Art. no.	PU	PG	Info
yellow	535491	1/80	4	



Snap collar for SCHUKO connector

- ▣ **Accessories from:** Rubber SCHUKO connector, art. no. 1740..., 1741... All-rubber SCHUKO connector, art. no. 1729... Heavy-duty all-rubber SCHUKO connector, art. no. 1730...

Version	Art. no.	PU	PG	Info
black	174196	10/120	4	



Replacement hinged lid for all-rubber SCHUKO connector

- ▣ **Accessories from:** All-rubber SCHUKO connector, art. no. 1729... Heavy-duty all-rubber SCHUKO connector, art. no. 1730...

Version	Art. no.	PU	PG	Info
black	173097	10/120	4	

Rubber plugs and connectors

- Modular system for easy extension
- Smart design



Rubber SCHUKO plug

16 A, AC 250 V, DIN 49441

Splash-proof plug.
With shatter-proof insert.
For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.



Version	Art. no.	PU	PG	Info
black	122151	10/80	4	



Rubber SCHUKO connector

16 A, AC 250 V, DIN 49440

With shatter-proof insert.
For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.

- ▣ **Accessories:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber connector, art. no. 174197. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Info
black	174091	10/80	4	



Rubber SCHUKO connector with snap collar

16 A, AC 250 V, DIN 49440

With shatter-proof insert.
For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.

- ▣ **Accessories:** Replacement hinged lid for all-rubber connector, art. no. 174197. Screwed joint, art. no. 535491.

Replacement part: Snap collar for SCHUKO connector, art. no. 174196.

Version	Art. no.	PU	PG	Info
black	174051	10/80	4	



Rubber SCHUKO connector with snap collar and hinged lid

16 A, AC 250 V, DIN 49440

Splash-proof connector. With shatter-proof insert.
Snap collar and hinged lid.
For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.



- ▣ **Accessories:** Screwed joint, art. no. 535491.

Replacement part: Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber connector, art. no. 174197.

Version	Art. no.	PU	PG	Info
black	174151	10/40	4	



Rubber SCHUKO plugs and connectors

16 A, AC 250 V, DIN 49440/49441

Splash-proof, all-rubber plugs and connectors with snap collar, hinged lid and screwed joint. Strain-resistant and shatter-proof plug-in connection.



- ▣ **Replacement part:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber connector, art. no. 174197. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Info
black/yellow	535451	1/12	4	



Screwed joint

For plugs and connectors with snap collars.

- ▣ **Accessories from:** SCHUKO plugs and connectors, art. no. 535451/93, 535593.

Version	Art. no.	PU	PG	Info
yellow	535491	1/80	4	



Snap collar for SCHUKO connector

▶ **Accessories from:** Rubber SCHUKO connector, art. no. 1740..., 1741... All-rubber SCHUKO connector, art. no. 1729... Heavy-duty all-rubber SCHUKO connector, art. no. 1730...

Version	Art. no.	PU	PG	Info
black	174196	10/120	4	



Replacement hinged lid for rubber connector

▶ **Accessories from:** Rubber SCHUKO connector, art. no. 1740..., 1741...

Version	Art. no.	PU	PG	Info
black	174197	10/120	4	

Export versions

- Modular system for easy extension.
- Handy design.



Rubber SCHUKO plug (DE, FR, BE)

16 A, AC 250 V, DIN 49441, CEE 7 Standard Sheet 7

With German and French earthing contact. Splash-proof plug.

With shatter-proof insert.

For cables up to 3 x 2.5 mm² H 07 RN-F and NSSHöu.



Version	Art. no.	PU	PG	Info
black	123251	10/60	4	

Still in the range



Heavy-duty all-rubber SCHUKO triple connector

16 A, AC 250 V, DIN 49440

Splash-proof industrial connector made from thermostable rubber. Moulded hook with holes for wall fixing. Snap collars and hinged lids, corrosion-resistant.

For cables up to 3x2.5 mm² H 07 RN-F and NSSHöu.

▶ **Replacement part:** Replacement cover for heavy-duty all-rubber SCHUKO triple connector, art. no. 178891.

Version	Art. no.	PU	PG	Info
black	178851	1/12	4	



Heavy-duty all-rubber SCHUKO triple connector with 5 m incoming cable

16 A, AC 250 V, DIN 49440

Splash-proof industrial connector made from thermostable rubber. Moulded hook with holes for wall fixing. Snap collars and hinged lids, corrosion-resistant.

With 5 m incoming cable 3 x 1.5 mm² H 07 RN-F and mounted all-rubber SCHUKO® plug, art. no. 122051.

▶ **Replacement part:** Replacement cover for heavy-duty all-rubber SCHUKO triple connector, art. no. 178891.

Version	Art. no.	PU	PG	Info
black	178899	1/5	4	



Replacement cover for heavy-duty all-rubber SCHUKO triple connector

▶ **Accessories from:** Heavy-duty all-rubber SCHUKO triple connector, art. no. 178851/99.

Version	Art. no.	PU	PG	Info
black	178891	1/150	4	



All-rubber SCHUKO triple suspended connector

16 A, AC 250 V, DIN 49440

Made from thermostable rubber. With moulded hook and hinged lids, corrosion-resistant. For cables up to 3 x 2.5 mm² H 07 RN-F.

▶ **Replacement part:** Replacement cover for all-rubber SCHUKO triple suspended connector, art. no. 179851.

▶ **Note:** The housing screws may only be tightened manually (tightening torque 0.8 Nm).

Version	Art. no.	PU	PG	Info
black	179851	1/21	4	



Replacement cover for all-rubber SCHUKO triple suspended connector

▶ **Accessories from:** All-rubber SCHUKO triple suspended connector, art. no. 179851.

Version	Art. no.	PU	PG	Info
black	179891	1/150	4	



SCHUKO rubber socket-outlet, surface-mounted

16 A, AC 250 V, DIN 49440

Made of thermostable rubber, with compression-moulded base, corrosion-resistant, shatter-proof. With screw terminals.

Version	Art. no.	PU	PG	Info
black	225251	10/70	4	

SCHUKO socket-outlets



SCHUKO triple socket-outlet, flush-mounted/surface-mounted

16 A, AC 250 V, DIN 49440

For installation in size 60 flush-mounted boxes. Dowel fixing also possible. With screw terminals. With claw and screw fixing.

Version	Art. no.	PU	PG	Info
white	271327	5/20	1.5	



SCHUKO triple socket-outlet

16 A, AC 250 V, DIN 49440

With plug-in terminals.

Note: For cavity wall installation: Use special box, art. no. 9062 from the Kaiser company in Schalksmühle, Germany.

Contents: Complete device with double mounting box and fixing screws.

Version	Art. no.	PU	PG	Info
white	231224	5/30	1	
polar white	231218	5/30	1	



Double mounting box

Plastic

Replaces two size 60 mounting boxes. Box is suitable for all conventional twin combinations.

Double mounting box for surface installation of PLANTEC with 8/18 function keys and display in solid walls.

Version	Art. no.	PU	PG	Info
	528668	1/30	1	



Impact-resistant SCHUKO socket-outlet, flush-mounted

16 A, AC 250 V, DIN 49440

Full, gently-curved top cover (100 x 100 mm). With screw terminals.

The dowel fixing provides protection in case the cable is pulled with excessive force.

Contents: Complete device.

Version	Art. no.	PU	PG	Info
white	270727	5/15	1	
polar white	270719	5/15	1	



SCHUKO e.l.c.b.-protected socket-outlet with hinged lid and improved protection against accidental contact

Integrated, improved protection against accidental contact in accordance with VDE 0620 Part 1 (replaces the previous designation "child protection").

Constructed in accordance with VDE 0664 (EN 61008). For the improvement of safety in existing installations according to VDE 0100 Part 410. Output to connect further loads.

For integration into a size 60 mounting box.

The e.l.c.b.-protected socket-outlet can be retrofitted for additional protection against damp using the gasket set.

Voltage: AC 230 V

Fault current: 30 mA

Max. current: 16 A

Short-circuit withstand capability: 3000 A

Type of protection: IP 20

Accessories: Gasket set, art. no. 232990.

Contents: Complete device.

Version	Art. no.	PU	PG	Info
polar white	232999	1/24	8.1	



Gasket set

The e.l.c.b.-protected socket-outlet can be retrofitted for additional protection against damp using the gasket set.

To be completed with: System Basis SCHUKO e.l.c.b.-protected socket-outlet with hinged lid, art. no. 232999.

Version	Art. no.	PU	PG	Info
Gasket set	232990	1/70	1	

SCHUKO plugs and sockets



SCHUKO plug

16 A, AC 250 V, DIN 49441

Small, shatter-proof quality plug with recessed grips.

Version	Art. no.	PU	PG	Info
white	122427	30/240	3.1	
grey	122463	30/180	3.1	
dark brazil	122415	30/180	3.1	



SCHUKO plug (DE, FR, BE)

16 A, AC 250 V, DIN 49441, CEE 7 Standard Sheet 7

With German and French earthing contact.

Small, shatter-proof quality plug with recessed grips.

Version	Art. no.	PU	PG	Info
grey	123363	30/180	3.1	



SCHUKO connector

16 A, AC 250 V, DIN 49440

Small, easy-to-grip connector with shatter-proof housing.

Version	Art. no.	PU	PG	Info
white	172427	15/120	3.1	
grey	172463	15/90	3.1	
dark brazil	172415	15/90	3.1	



Shatter-proof SCHUKO plug

16 A, AC 250 V, DIN 49441

With lateral insertion and one-piece, shatter-proof housing.

Version	Art. no.	PU	PG	Info
white	120927	25/200	3.1	
dark brazil	120915	25/150	3.1	



Shock-proof SCHUKO plug with bend protection sleeve

16 A, AC 250 V, DIN 49441

With lateral insertion, bend protection sleeve and one-piece, shatter-proof housing.

Version	Art. no.	PU	PG	Info
grey	120963	20/120	3.1	



SCHUKO angled plug with toggle switch

16 A, AC 250 V, DIN 49441

With 2-pole toggle switch. Shatter-proof lid.

Version	Art. no.	PU	PG	Info
white	128427	15/90	3	



SCHUKO angled plug with toggle switch and control lamp

16 A, AC 250 V, DIN 49441

With 2-pole toggle switch. Shatter-proof lid, control light.

Version	Art. no.	PU	PG	Info
white	128474	15/90	3	



SCHUKO angled plug with toggle switch (DE, FR, BE)

16 A, AC 250 V, DIN 49441, CEE 7 Standard Sheet 7

With German and French earthing contact. With 2-pole toggle switch. Shatter-proof lid.

Version	Art. no.	PU	PG	Info
white	128527	15/90	3	



SCHUKO angled plug with toggle switch, control lamp (DE, FR, BE)

16 A, AC 250 V, DIN 49441, CEE 7 Standard Sheet 7

With German and French/Belgian earthing contact.

With 2-pole toggle switch.

Shock-proof lid, control light.

Version	Art. no.	PU	PG	Info
white	128574	15/90	3	



PVC SCHUKO plug

16 A, AC 250 V, DIN 49441

Splash-proof plug.

Large version, with bend protection sleeve.



Version	Art. no.	PU	PG	Info
polar white	125462	15/90	3.1	
grey	125463	15/120	3.1	



PVC SCHUKO plug (DE, FR, BE)

16 A, AC 250 V, DIN 49441, CEE 7 Standard Sheet 7

With German and French/Belgian earthing contact.

Splash-proof.

Large design, with bend protection sleeve.



Version	Art. no.	PU	PG	Info
grey	123463	15/90	3.1	



PVC SCHUKO connector

16 A, AC 250 V, DIN 49440

Large version, with bend protection sleeve.

Version	Art. no.	PU	PG	Info
polar white	173762	10/60	3.1	
grey	173763	10/60	3.1	



Mobile garden socket-outlet without incoming cable

16 A, AC 250 V, DIN 49440

Splash-proof SCHUKO double socket-outlet.

An ideal current distributor for garden parties, for mowing the lawn and so on.

Stable, weather-resistant plastic bracket.

With screw terminals.



Version	Art. no.	PU	PG	Info
black/grey	599893	1/3	3.1	



Mobile garden socket-outlet with 5 m incoming cable

16 A, AC 250 V, DIN 49440

Splash-proof SCHUKO double socket-outlet. An ideal power distribution system for garden parties, cutting the lawn etc. With 5 m incoming cable 3x1 mm² H 05 RN-F and integral rubber SCHUKO plug. Stable, weather-resistant plastic bracket.

With screw terminals.

Version	Art. no.	PU	PG	Info
black/grey	599894	1/3	3.1	

PERILEX plugs and connectors

- For many applications there is no time limit on the use of PERILEX.
- Blocks of flats, business premises, hotels, laboratories, large kitchens and similar plants can even today still be safely installed to modern standards using PERILEX.
- Splash-proof, similar to IP 44.



PERILEX plug

16 A, AC 400 V, DIN 49446

Version	Art. no.	PU	PG	Info
white	134027	10/80	5	



PERILEX connector

16 A, AC 400 V, DIN 49445

Version	Art. no.	PU	PG	Info
white	183027	10/60	5	



PERILEX angled plug

16 A, AC 400 V, DIN 49446

Version	Art. no.	PU	PG	Info
white	130027	10/60	5	



PERILEX socket-outlet, flush-mounted

16 A, AC 400 V, DIN 49445

With retaining ring.
For integration into a size 70 mounting box.

Version	Art. no.	PU	PG	Info
white	250427	10/30	5	



PERILEX socket-outlet, flush-mounted

16 A, AC 400 V, DIN 49445

Version	Art. no.	PU	PG	Info
white	255027	10/50	5	



All-rubber PERILEX plug

16 A, AC 400 V, DIN 49446

Splash-proof. With membrane seal. Robust plug with rubber lip. Corrosion-resistant and shatter-proof.

IP44

Version	Art. no.	PU	PG	Info
black	134251	10/30	5	



All-rubber PERILEX connector

16 A, AC 400 V, DIN 49445

Robust connector.
Corrosion-resistant and shatter-proof.
With membrane seal.

Version	Art. no.	PU	PG	Info
black	183251	10/30	5	



PVC PERILEX plug

16 A, AC 400 V, DIN 49446

Shatter-proof contact bracket insert made from high-quality, electric insulation material. With membrane seal.



Version	Art. no.	PU	PG	Info
grey	134163	10/30	5	



PVC PERILEX connector

16 A, AC 400 V, DIN 49445

Shatter-proof contact bracket insert made from high-quality, electric insulation material. With membrane seal.

Version	Art. no.	PU	PG	Info
grey	183163	10/30	5	



PERILEX socket-outlet, flush-mounted, with hinged lid

16 A, AC 400 V, DIN 49445

Splash-proof.
With shatter-proof hinged lid.



Contents: With mounting box for large plaster adjustment.

Version	Art. no.	PU	PG	Info
white	253227	10/30	5	



PERILEX socket-outlet, surface-mounted, with hinged lid

16 A, AC 400 V, DIN 49445

Splash-proof.
With shatter-proof hinged lid.



Version	Art. no.	PU	PG	Info
grey	258329	10/30	5	



Slide with gland

For cables and leads.

- ▶ **To be completed with:** PERILEX socket-outlet, surface-mounted, with hinged lid, art. no. 258329.

Version	Art. no.	PU	PG	Info
grey	258309	10/300	5	



Slide without gland

For cables and leads.

- ▶ **To be completed with:** PERILEX socket-outlet, surface-mounted, with hinged lid, art. no. 258329.

Version	Art. no.	PU	PG	Info
grey	258311	10/400	5	



PERILEX angled plug, 25 A

25 A, AC 400 V, DIN 49448

Made from pressed material.

Version	Art. no.	PU	PG	Info
white	130527	10/20	5	



PERILEX socket-outlet, flush-mounted, 25 A

25 A, AC 400 V, DIN 49447

With retaining ring.

- ▶ **Accessories:** Insulating mounting box, art. no. 528304.

Version	Art. no.	PU	PG	Info
white	250327	1/20	5	



Insulating mounting box

- ▶ **To be completed with:** PERILEX socket-outlet, flush-mounted, 25 A, art. no. 250327.

Version	Art. no.	PU	PG	Info
black	528304	1/30	5	

HNA plugs and connectors

- The HNA plugs and connectors are indispensable in special circuits to differentiate between normal circuits.
- HNA plugs and connectors have proved particularly suitable for powering EDP systems via a special circuit.



HNA plug

10 A, 250 V, C 220 DIN 89321

Version	Art. no.	PU	PG	Info
grey	105129	10/80	7	



HNA angled plug

10 A, 250 V, C 220 DIN 89321

Splash-proof, comparable to IP 44



Version	Art. no.	PU	PG	Info
white	105327	10/100	7	



HNA socket-outlet insert

10 A, 250 V, B 220 DIN 89321

For System Basis.
For socket-outlets where it is essential that they are not interchanged.

- ▶ **Adapters:** Can be integrated into System Design using the adapter, art. no. 5180..., and into the OCTOCOLOR range using the adapter, 5170... Can be installed in damp rooms or outdoors using the protective cover with gasket, art. no. 5172...

Version	Art. no.	PU	PG	Info
white	204074	10/40	7	
polar white	204019	10/40	7	



HNA socket-outlet insert

10 A, 250 V, B 220 DIN 89321

For System M.
For socket-outlets where it is essential that they are not interchanged.

Version	Art. no.	PU	PG	Info
---------	----------	----	----	------

▶ Thermoplastic brilliant

white, glossy	204944	10/40	7	
polar white, glossy	204919	10/40	7	
active white, glossy	204925	10/40	7	

▶ Thermoplastic classy matt

white	204144	10/40	7	
polar white	204119	10/40	7	

- ▶ **Duroplastic, highly scratch-resistant: With this article, use thermoplastic brilliant**



HNA socket-outlet, surface-mounted

10 A, 250 V~, A 220 DIN 89321

For socket-outlets where it is essential that they are not interchanged.

Contents: With cable and mini-trunking entry (15 mm).

Version	Art. no.	PU	PG	Info
white	205444	10/70	7	



HNA socket-outlet, surface-mounted

10 A, 250 V~, A 220 DIN 89321

Splash-proof.
For socket-outlets where it is essential that they are not interchanged.



Version	Art. no.	PU	PG	Info
grey	208429	10/50	7	