

Range for damp locations

- Plug-in terminals even for socket-outlets.
- All socket-outlet hinged lids, switches and light signals can be retrofitted with a labelling field.
- All bases are removable.
- Switch inserts with connecting terminals to VDE 0632
- Can be illuminated as defined by German workplace regulations of 20.03.1975.
- Socket-outlets with connecting terminals to VDE 0620 part 1.
- Notes on materials:
Tough thermoplastic housing.
All external metal parts are made of rustproof material.

▣ **Material:** Thermoplastic.

▣ **Technical Information:** AQUASTAR dimensions (⇒ p. 442)

Switches, push-buttons and accessories

▣ **Technical Information:** Circuit diagrams for installation of switches and push-buttons (⇒ p. 427)



Rocker switch
10 AX, AC 250 V

IP 44

Version	Art. no.	PU	PG	Info
two-way, light grey	340639	10/60	2	
intermediate, light grey	340739	10/40	2	
one-way, 2-pole, light grey	340239	10/40	2	



Rocker switch
10 AX, AC 250 V

IP 44

Version	Art. no.	PU	PG	Info
two-circuit, light grey	340539	10/40	2	



Rocker switch
16 AX, AC 400 V

Illuminated.
With screw terminals.

IP 44

▣ **Accessories:** Light attachment, art. no. 396376.

Version	Art. no.	PU	PG	Info
one-way, 3-pole, light grey	340339	10/40	2	



Light attachment for 3-pole switch
AC 400 V, 1.25 mA

For 3-pole switch.
Contacts the outside terminals (400 V).

▣ **To be completed with:** Rocker switch insert, art. no. 311300.
Rocker switch, art. no. 340339. Rocker control switch, art. no. 372375.

▣ **Contents:** With neon lamp.

Version	Art. no.	PU	PG	Info
AC 400 V, 1.25 mA	396376	5/1020	1	



Rocker control switch
10 AX, AC 250 V

Can also be used as a 1-pole, one-way control switch.

Can be used as a heating emergency switch with the labelling insert supplied.

IP 44

▣ **Contents:** With neon lamp (spot light) and labelling insert, art. no. 395939.

Version	Art. no.	PU	PG	Info
two-way, light grey	342639	10/40	2	
one-way, 2-pole, light grey	342239	10/40	2	



Rocker button
10 A, 250 V AC

IP 44

▣ **Contents:** With labelling insert "Light". We also supply 5 labelling inserts for every 5 buttons: 1 door, 3 bell and 1 neutral.

Version	Art. no.	PU	PG	Info
make contact, 1-pole, light grey	344039	10/40	2	
make contact, 1-pole with separate signalling contact and integral neon lamp, light grey	344839	10/40	2	
two-way, 1-pole, light grey	344939	10/40	2	



Light attachment for AQUASTAR

Spot lighting Ø 22.5 mm.

▣ **Contents:** With neon lamp.

Version	Art. no.	PU	PG	Info
AC 230 V, 0.65 mA	396776	10/1000	2	
12 V/ 2 W	396772	5/300	2	
24 V/ 2 W	396774	5/300	2	



Long light attachment

AC 230 V

With fitted neon lamp.
Current consumption 3.5 mA.

Version	Art. no.	PU	PG	Info
AC 230 V	396876	5/300	2	



Heating emergency switch

10 AX, AC 250 V

With imprint "Heating emergency switch".

IP 44

Contents: With long light attachment and double entry for cable and leads.

Version	Art. no.	PU	PG	Info
two-way, light grey	342694	10/40	2	
one-way, 2-pole, light grey	342294	10/40	2	



Heating emergency switch

16 AX, AC 400 V

With imprint "Heating emergency switch".

IP 44

Contents: With neon lamp and double entry for cable and leads.

Version	Art. no.	PU	PG	Info
one-way, 3-pole, light grey	340394	10/40	2	



Two-way pull-cord switch

10 AX, AC 250 V

Duroplastic housing.

IP 44

Version	Art. no.	PU	PG	Info
two-way, light grey	346629	5/30	2	

Roller shutter switches

Technical Information: Roller shutter switch and push-button (⇒ p. 462)



Roller shutter rocker switch

10 A, 250 V AC

With mechanical reverse lock-out and electrical interlock.

IP 44

Version	Art. no.	PU	PG	Info
1-pole, light grey	341539	10/40	2	



Roller shutter rocker button

10 A, 250 V AC

With mechanical reverse lock-out and electrical interlock.

IP 44

Version	Art. no.	PU	PG	Info
1-pole, light grey	345539	10/40	2	



Momentary/maintained-contact switch for roller shutters for cylinder locks

10 A, 250 V AC

For standard semi-cylinder locks of 40 mm in length.

IP 44

Contents: Without lock.

Version	Art. no.	PU	PG	Info
2-pole, light grey	347639	1/24	8	



Roller shutter push-button for cylinder locks

10 A, 250 V AC

For standard semi-cylinder locks of 40 mm in length.

IP 44

Contents: Without lock.

Version	Art. no.	PU	PG	Info
2-pole, light grey	347939	1/24	8	

SCHUKO socket-outlets



SCHUKO socket-outlet

16 A, AC 250 V, DIN 49440

With labelling option and labelling insert.
With plug-in terminals.

IP44

▣ **Accessories:** Labelling insert, art. no. 235539.

Version	Art. no.	PU	PG	Info
light grey	238039	10/60	2	



SCHUKO socket-outlet, lockable

16 A, AC 250 V, DIN 49440

With labelling option and labelling insert.
With plug-in terminals.

IP44

▣ **Accessories:** Labelling insert, art. no. 235539.

▣ **Contents:** With security lock, 2 keys per socket-outlet.

Version	Art. no.	PU	PG	Info
different locks, light grey	238139	1/30	2	
identical locks, lock no. 200, light grey	238104	1/30	2	
2 identical locks, double set, light grey	238105	1/18	2	



IP44

SCHUKO double socket-outlet, horizontal arrangement

16 A, AC 250 V, DIN 49440

Arranged horizontally and wired together.
With labelling option and labelling insert.
With 4 cable entries.
With plug-in terminals.

▣ **Accessories:** Labelling insert, art. no. 235539.

Version	Art. no.	PU	PG	Info
light grey	239039	5/30	2	



SCHUKO double socket-outlet, vertical arrangement

16 A, AC 250 V, DIN 49440

Arranged vertically and wired together.
With labelling option and labelling insert.
With 2 cable entries.
With plug-in terminals.

IP44

▣ **Accessories:** Labelling insert, art. no. 235539.

Version	Art. no.	PU	PG	Info
light grey	239139	5/30	2	



IP44

SCHUKO triple socket-outlet

16 A, AC 250 V, DIN 49440

With labelling option and labelling insert.
The bases are wired together. With 5 cable entries.
The inserts can be replaced with any other devices in the AQUASTAR range.
With plug-in terminals.

▣ **Accessories:** Labelling insert, art. no. 235539.

Version	Art. no.	PU	PG	Info
light grey	239739	1/14	2	



IP44

Combination SCHUKO socket-outlet/two-way switch

SCHUKO socket-outlet: 16 A, AC 250 V, DIN 49440.

Combined with two-way switch: 10 AX, AC 250 V.
The inserts can be replaced with any other devices in the AQUASTAR range.

▣ **Accessories:** Labelling insert, art. no. 235539.

Version	Art. no.	PU	PG	Info
light grey	227239	5/30	2	

Accessories



Label set

All AQUASTAR switches and AQUASTAR light signals E 14 can be labelled using these labelling inserts. The labelling insert is suitable for use with a type-writer.

Contents: 5 white inserts.

Version	Art. no.	PU	PG	Info
neutral	395539	1/1000	2	
light	395639	1/1000	2	
door	395739	1/1000	2	
bell	395839	1/1000	2	
heating emergency switch	395939	1/1000	2	
for 3-pole, one-way switch 340339/94	395339	1/1000	2	



Labelling insert

All AQUASTAR socket-outlets can be labelled using the labelling insert. The labelling insert is suitable for use with a type-writer.

Contents: Transparent labelling insert and labelling strips.

Version	Art. no.	PU	PG	Info
white	235539	10/1000	2	



Light signal E 14

AC 250 V, max. 5 W

With flat, red hood for max. 5 watt. For neon and incandescent lamps of max. 38 mm in length. Can be retrofitted with a shatter-proof dome for max. 10 watt.

IP 44

To be completed with: Incandescent lamp E 14, art. no. 396676. Dome for light signal E 14, art. no. 396611/12/13.

Accessories: Dome for light signal E14, art. no. 396611/12/13.

Contents: Without neon lamp.

Version	Art. no.	PU	PG	Info
light grey	348039	1/30	2	



Incandescent lamp E 14

AC 250 V, 5 W

Particularly suited to light signal E 14 with flat hood.

To be completed with: Light signal E 14 insert, art. no. 348039.

Version	Art. no.	PU	PG	Info
AC 230 V, 5 watts	396676	5/1020	2	



Dome for light signal E 14

Break-proof, high version for neon lamps in accordance with DIN 49850 and tubular lamps in accordance with DIN 49852, form A up to a max. of 10 watts, e.g. ERG type RL/E 14, 10 W.

To be completed with: Light signal E 14 insert, art. no. 378075. Light signal E 14 insert, art. no. 348039.

Version	Art. no.	PU	PG	Info
green	396612	2/80	2	
red	396611	2/80	2	
clear	396613	2/80	2	



Double entry

For cables and leads.

Version	Art. no.	PU	PG	Info
grey	536062	10/1000	2	



Slide with gland

For M20 x 1.5 steel armoured conduit with thread or M20 x 1.5 compression gland.

Version	Art. no.	PU	PG	Info
grey	535563	10/300	2	



Connecting element

For close arrangement of several devices.

Version	Art. no.	PU	PG	Info
grey	535962	10/500	2	



Conduit entry

For plastic tubes in accordance with 49016. Internal diameter 18.7 mm and external diameter 25 mm.

Version	Art. no.	PU	PG	Info
grey	534062	10/240	2	



Mini-trunking entry

For 15 x 15 mm ducts.

Version	Art. no.	PU	PG	Info
grey	534162	10/240	2	