

# COOKER AND APPLIANCE CONNECTION BOXES RUBBER SCHUKO® PLUGS AND CONNECTORS FOR FIXED CONNECTIONS



## **Cooker and appliance connection boxes**

Whether flush- or surface-mounted with simple or multiple connection boxes, Merten cooker and appliance connection boxes meet all professional requirements and guarantee a safe, reliable and robust connection, not least thanks to their shatter-proof covers.

## **Plugs and connectors**

Indestructible. Merten rubber SCHUKO® plugs and connectors are very durable, both in day-to-day use in the workshop and on large-scale building sites. Merten has suitable plugs and connectors for every area and type of application.

Thanks to a modular assembly system, the snap collars, screwed joints and hinged lids are compatible with all plugs and connectors and can be easily replaced. All Merten rubber plugs and connectors bear the hammer symbol as well as all recognised quality marks. Guaranteed product quality you can rely on day after day.

# CONTENTS



Cooker and appliance connection box



Plugs and connectors

## 376 COOKER AND APPLIANCE CONNECTION BOXES

- 376 Cooker and appliance connection boxes
- 377 Cable junction boxes

## 378 RUBBER SCHUKO PLUGS AND CONNECTORS

- 378 Heavy-duty all-rubber plugs and connectors
- 379 All-rubber plugs and connectors
- 380 Rubber plugs and connectors
- 381 Export versions
- 381 Still in the range

## 383 SCHUKO PLUGS AND CONNECTORS

- 383 SCHUKO socket-outlets
- 384 SCHUKO plugs and sockets

## 386 PLUGS AND CONNECTORS

- 386 PERILEX plugs and connectors
- 387 HNA plugs and connectors
- 388 CEE 17 plugs and connectors

## Cooker and appliance connection boxes



### Cooker connection box, flush-mounted

Nominal cross-section 2.5 mm<sup>2</sup>

Particularly flat design. With shatter-proof lid and snap lock, removable terminal block with 5 double terminals.

IP20

**Technical Information:** Cooker sockets (⇒ p. 410)

**Note:** If using extension claws art. no. 533591, also fits size 70 flush-mounted boxes.

Version	Art. no.	PU	PG	Mat.	Info
polar white	520427	5/60	6.1		



### Cooker connection box, flush- and surface-mounted

Nominal cross-section 2.5 mm<sup>2</sup>

With shatter-proof lid and snap lock. Screw and claw fixing for size 60 and 70 flush-mounted boxes with removable claws.

Large, clear wiring compartment.

Dowel fixing and cable entry from above also possible. Strain relief.



IP20

**Technical Information:** Cooker sockets (⇒ p. 410)

Version	Art. no.	PU	PG	Mat.	Info
polar white	520619	5/40	6.1	TP	



### Cooker connection box, flush-mounted

Nominal cross-section 4 mm<sup>2</sup>

IP20

**Contents:** With plaster adjustment ring, insulating mounting box, protective cover for plaster.

Version	Art. no.	PU	PG	Mat.	Info
white	520227	2/22	6		



### Cooker connection box, flush-mounted, IP 21

Nominal cross-section 4 mm<sup>2</sup>

Terminal block with 5 double terminals.

Gasket on the underside of the cover and on the cable outlet.

IP21

Version	Art. no.	PU	PG	Mat.	Info
white	520327	2/22	6		




### Cooker connection box, surface-mounted

Nominal cross-section 6 mm<sup>2</sup>

With 5-pole terminal block.

IP20

Version	Art. no.	PU	PG	Mat.	Info
white	520827	5/30	6		



IP20

### Three-section appliance connection box, flush- and surface-mounted

Nominal cross-section 2.5 mm<sup>2</sup>

2 shatter-proof lids with snap lock, 3 removable terminal blocks with 12 double terminals.

Large, clearly visible wiring compartments.

Screw and claw fixing for size 60 and size 70 flush-mounted boxes (brick walls, cavity walls and concrete), with removable spreading claws.

Dowel fixing also possible.

**Technical Information:** Cooker sockets (⇒ p. 410)

Version	Art. no.	PU	PG	Mat.	Info
polar white	521044	5/20	6		



IP20

### Three-section appliance connection box, flush-mounted

Nominal cross-section 2.5 mm<sup>2</sup>

2 x 5 double terminals, removable, to connect electric storage heaters or 2 different electrical household appliances.

Version	Art. no.	PU	PG	Mat.	Info
white	521427	5/10	6		



IP20

### Three-section appliance connection box, flush-mounted, large terminal compartment

Nominal cross-section 2.5 mm<sup>2</sup>

3 x 5 double terminals, 3 separate connection chambers to connect electric storage heaters or to power 3 different electrical household appliances.

Version	Art. no.	PU	PG	Mat.	Info
white	521927	1/12	6		



## Terminal block

5-pole, for 2.5 mm<sup>2</sup>  
Double terminals with hole diameter 3.8 mm.  
Very versatile.

Accessories from: Cooker connection box, art. no. 520427, 521044, 521427, 521927.

Version	Art. no.	PU	PG	Mat.	Info
white	<b>520900</b>	10/480	6		



IP20

## GEH appliance connection box, flush-mounted

Nominal cross-section 2.5 mm<sup>2</sup>

For controlled electric heaters and electric storage heaters. 13 double terminals and protective conductor bar with 6 contact points.

Version	Art. no.	PU	PG	Mat.	Info
black	<b>520599</b>	1/8	6		

### Cable junction boxes

- Cable junction boxes allow cables of different cross-sections, from 3 x 1.5 mm<sup>2</sup> to 5 x 6 mm<sup>2</sup>, to be connected safely and quickly.



## Cable junction box

5 x 2.5 mm<sup>2</sup>, ø 27.5 mm

IP54

For fixed cabling. With strain relief.  
Certified in line with VDE 0606.

Version	Art. no.	PU	PG	Mat.	Info
grey/5 x 2.5 mm <sup>2</sup>	<b>526129</b>	10/200	7		



## Cable junction box

5 x 6 mm<sup>2</sup>, ø 34.5 mm

IP54

For fixed cabling. With strain relief.  
Certified in line with VDE 0606.

Version	Art. no.	PU	PG	Mat.	Info
grey/5 x 6 mm <sup>2</sup>	<b>526229</b>	10/100	7		

## SCHUKO rubber plugs and connectors for wind and weather.

- According to the regulations regarding electrical power systems (VDE 0100 § 55e), the only connectors and plugs permissible on building sites are those that conform to DIN 49440 and 49441 and are approved "for harsh conditions". These plugs and connectors bear the hammer symbol.
- IP 44 splashwater protection is achieved in conjunction with a snap collar and hinged lid.
- Modular system for the extension of SCHUKO plugs and connectors with snap collar, hinged lid and screwed joint.
- Material: Natural rubber
- Uniform design
- Easy grip thanks to optimised shaping of the surface
- Simple and quick installation thanks to easily accessible screws
- The strain relief allows cables with different diameters to be used

## Heavy-duty all-rubber plugs and connectors

- Extra large terminal compartment
- Rubber insert for use in extreme conditions
- Screws at the front for ultimate tensile strength
- Modular system for easy extension
- Smart design



## Heavy-duty all-rubber SCHUKO plug

16 A, AC 250 V, DIN 49441

Splash-proof plug. Robust design. Bend protection sleeve with membrane seal. Shatter-proof, corrosion-resistant. For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.



Version	Art. no.	PU	PG	Mat.	Info
black	123551	10/80	4		



## Heavy-duty all-rubber SCHUKO connector

16 A, AC 250 V, DIN 49440

Robust design. Bend protection sleeve with membrane seal. Shatter-proof, corrosion-resistant. For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.

- ▣ **Accessories:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Mat.	Info
black	173091	10/60	4		



## Heavy-duty all-rubber SCHUKO connector with snap collar

16 A, AC 250 V, DIN 49440

Robust design. Bend protection sleeve with membrane seal. Shatter-proof, corrosion-resistant. For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.

- ▣ **Accessories:** Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

**Replacement part:** Snap collar for SCHUKO connector, art. no. 174196.

Version	Art. no.	PU	PG	Mat.	Info
black	173092	10/40	4		



## Heavy-duty all-rubber SCHUKO connector with snap collar and hinged lid

16 A, AC 250 V, DIN 49440

Splash-proof connector. Robust design. Bend protection sleeve with membrane seal. Shatter-proof, corrosion-resistant.

For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.



- ▣ **Accessories:** Screwed joint, art. no. 535491.

**Replacement part:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097.

Version	Art. no.	PU	PG	Mat.	Info
black	173051	10/60	4		



## Heavy-duty all-rubber SCHUKO plugs and connectors

16 A, AC 250 V, DIN 49440/49441

Splash-proof, heavy-duty all-rubber plugs and connectors with snap collar, hinged lid and screwed joint. Robust design. Bend protection sleeve with membrane seal. Shatter-proof, corrosion-resistant. For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.



- ▣ **Replacement part:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Mat.	Info
black/yellow	535593	1/12	4		



## Screwed joint

For plugs and connectors with snap collars.

- ▣ **Accessories from:** SCHUKO plugs and connectors, art. no. 535451/93, 535593.

Version	Art. no.	PU	PG	Mat.	Info
yellow	535491	1/80	4		



## Snap collar for SCHUKO connector

Accessories from: Rubber SCHUKO connector, art. no. 1740..., 1741... All-rubber SCHUKO connector, art. no. 1729... Heavy-duty all-rubber SCHUKO connector, art. no. 1730...

Version	Art. no.	PU	PG	Mat.	Info
black	174196	10/120	4		



## Replacement hinged lid for all-rubber SCHUKO connector

Accessories from: All-rubber SCHUKO connector, art. no. 1729... Heavy-duty all-rubber SCHUKO connector, art. no. 1730...

Version	Art. no.	PU	PG	Mat.	Info
black	173097	10/120	4		

### All-rubber plugs and connectors

- Extra large terminal compartment
- Rubber insert for use in extreme conditions
- Screws at the front for ultimate tensile strength
- Modular system for easy extension
- Smart design



## All-rubber SCHUKO plug

16 A, AC 250 V, DIN 49441

Splash-proof plug. Robust design, corrosion-resistant. Highly shatter-resistant. For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.



Version	Art. no.	PU	PG	Mat.	Info
black	122051	10/80	4		



## All-rubber SCHUKO connector

16 A, AC 250 V, DIN 49440

Robust design, corrosion-resistant. Highly shatter-resistant.

For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.

Accessories: Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Mat.	Info
black	172991	10/80	4		



## All-rubber SCHUKO connector with snap collar

16 A, AC 250 V, DIN 49440

Robust design, corrosion-resistant. Highly shatter-resistant.

For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.

Accessories: Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Replacement part: Snap collar for SCHUKO connector, art. no. 174196.

Version	Art. no.	PU	PG	Mat.	Info
black	172951	10/80	4		



## All-rubber SCHUKO connector with snap collar and hinged lid

16 A, AC 250 V, DIN 49440

Splash-proof connector. Robust design, corrosion-resistant. Highly shatter-resistant.

For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.



Accessories: Screwed joint, art. no. 535491.

Replacement part: Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097.

Version	Art. no.	PU	PG	Mat.	Info
black	172993	10/40	4		



## All-rubber SCHUKO plugs and connectors

16 A, AC 250 V, DIN 49440/49441

Splash-proof, all-rubber plugs and connectors with snap collar, hinged lid and screwed joint. Robust design, corrosion-resistant. Highly shatter-resistant.

For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.



Replacement part: Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber SCHUKO connector, art. no. 173097. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Mat.	Info
black/yellow	535493	1/12	4		



## Screwed joint

For plugs and connectors with snap collars.

Accessories from: SCHUKO plugs and connectors, art. no. 535451/93, 535593.

Version	Art. no.	PU	PG	Mat.	Info
yellow	535491	1/80	4		



## Snap collar for SCHUKO connector

- ▣ **Accessories from:** Rubber SCHUKO connector, art. no. 1740..., 1741... All-rubber SCHUKO connector, art. no. 1729... Heavy-duty all-rubber SCHUKO connector, art. no. 1730...

Version	Art. no.	PU	PG	Mat.	Info
black	<b>174196</b>	10/120	4		



## Replacement hinged lid for all-rubber SCHUKO connector

- ▣ **Accessories from:** All-rubber SCHUKO connector, art. no. 1729... Heavy-duty all-rubber SCHUKO connector, art. no. 1730...

Version	Art. no.	PU	PG	Mat.	Info
black	<b>173097</b>	10/120	4		

### Rubber plugs and connectors

- Modular system for easy extension
- Smart design



## Rubber SCHUKO plug

**16 A, AC 250 V, DIN 49441**

Splash-proof plug.  
With shatter-proof insert.  
For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.



Version	Art. no.	PU	PG	Mat.	Info
black	<b>122151</b>	10/80	4		



## Rubber SCHUKO connector

**16 A, AC 250 V, DIN 49440**

With shatter-proof insert.  
For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.

- ▣ **Accessories:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber connector, art. no. 174197. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Mat.	Info
black	<b>174091</b>	10/80	4		



## Rubber SCHUKO connector with snap collar

**16 A, AC 250 V, DIN 49440**

With shatter-proof insert.  
For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.

- ▣ **Accessories:** Replacement hinged lid for all-rubber connector, art. no. 174197. Screwed joint, art. no. 535491.

**Replacement part:** Snap collar for SCHUKO connector, art. no. 174196.

Version	Art. no.	PU	PG	Mat.	Info
black	<b>174051</b>	10/80	4		



## Rubber SCHUKO connector with snap collar and hinged lid

**16 A, AC 250 V, DIN 49440**

Splash-proof connector. With shatter-proof insert.  
Snap collar and hinged lid.  
For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.



- ▣ **Accessories:** Screwed joint, art. no. 535491.

**Replacement part:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber connector, art. no. 174197.

Version	Art. no.	PU	PG	Mat.	Info
black	<b>174151</b>	10/40	4		



## Rubber SCHUKO plugs and connectors

**16 A, AC 250 V, DIN 49440/49441**

Splash-proof, all-rubber plugs and connectors with snap collar, hinged lid and screwed joint. Strain-resistant and shatter-proof plug-in connection.



- ▣ **Replacement part:** Snap collar for SCHUKO connector, art. no. 174196. Replacement hinged lid for all-rubber connector, art. no. 174197. Screwed joint, art. no. 535491.

Version	Art. no.	PU	PG	Mat.	Info
black/yellow	<b>535451</b>	1/12	4		



## Screwed joint

For plugs and connectors with snap collars.

- ▣ **Accessories from:** SCHUKO plugs and connectors, art. no. 535451/93, 535593.

Version	Art. no.	PU	PG	Mat.	Info
yellow	<b>535491</b>	1/80	4		



## Snap collar for SCHUKO connector

**Accessories from:** Rubber SCHUKO connector, art. no. 1740..., 1741... All-rubber SCHUKO connector, art. no. 1729... Heavy-duty all-rubber SCHUKO connector, art. no. 1730...

Version	Art. no.	PU	PG	Mat.	Info
black	<b>174196</b>	10/120	4		



## Replacement hinged lid for rubber connector

**Accessories from:** Rubber SCHUKO connector, art. no. 1740..., 1741...

Version	Art. no.	PU	PG	Mat.	Info
black	<b>174197</b>	10/120	4		

### Export versions

- Modular system for easy extension.
- Handy design.



## Rubber SCHUKO plug (DE, FR, BE) 16 A, AC 250 V, DIN 49441, CEE 7 Standard Sheet 7

With German and French earthing contact. Splash-proof plug.

With shatter-proof insert. For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.



Version	Art. no.	PU	PG	Mat.	Info
black	<b>123251</b>	10/60	4		

### Still in the range



## Heavy-duty all-rubber SCHUKO triple connector

**16 A, AC 250 V, DIN 49440**

Splash-proof industrial connector made from thermostable rubber. Moulded hook with holes for wall fixing. Snap collars and hinged lids, corrosion-resistant.

For cables up to 3x2.5 mm<sup>2</sup> H 07 RN-F and NSSHöu.



**Replacement part:** Replacement cover for heavy-duty all-rubber SCHUKO triple connector, art. no. 178891.

Version	Art. no.	PU	PG	Mat.	Info
black	<b>178851</b>	1/12	4		



## Heavy-duty all-rubber SCHUKO triple connector with 5 m incoming cable

**16 A, AC 250 V, DIN 49440**

Splash-proof industrial connector made from thermostable rubber. Moulded hook with holes for wall fixing. Snap collars and hinged lids, corrosion-resistant.

With 5 m incoming cable 3 x 1.5 mm<sup>2</sup> H 07 RN-F and mounted all-rubber SCHUKO® plug, art. no. 122051.



**Replacement part:** Replacement cover for heavy-duty all-rubber SCHUKO triple connector, art. no. 178891.

Version	Art. no.	PU	PG	Mat.	Info
black	<b>178899</b>	1/5	4		



## Replacement cover for heavy-duty all-rubber SCHUKO triple connector

**Accessories from:** Heavy-duty all-rubber SCHUKO triple connector, art. no. 178851/99.

Version	Art. no.	PU	PG	Mat.	Info
black	<b>178891</b>	1/150	4		



## All-rubber SCHUKO triple suspended connector

**16 A, AC 250 V, DIN 49440**

Made from thermostable rubber. With moulded hook and hinged lids, corrosion-resistant. For cables up to 3 x 2.5 mm<sup>2</sup> H 07 RN-F.



**Replacement part:** Replacement cover for all-rubber SCHUKO triple suspended connector, art. no. 179851.

Version	Art. no.	PU	PG	Mat.	Info
black	<b>179851</b>	1/21	4		



## Replacement cover for all-rubber SCHUKO triple suspended connector

**Accessories from:** All-rubber SCHUKO triple suspended connector, art. no. 179851.

Version	Art. no.	PU	PG	Mat.	Info
black	<b>179891</b>	1/150	4		



## SCHUKO rubber socket-outlet, surface-mounted

**16 A, AC 250 V, DIN 49440**

Made of thermostable rubber, with compression-moulded base, corrosion-resistant, shatter-proof. With screw terminals as connecting terminals in accordance with VDE 0620 Part 1.

Version	Art. no.	PU	PG	Mat.	Info
black	<b>225251</b>	10/70	4		

- Notes on materials:  
TP: Shatter-proof thermoplastic.  
DP: Highly scratch-resistant duroplastic.

## SCHUKO socket-outlets



### SCHUKO triple socket-outlet, flush-mounted/surface-mounted

**16 A, AC 250 V, DIN 49440**

For installation in size 60 flush-mounted boxes.  
Dowel fixing also possible.  
With screw terminals as connecting terminals in accordance with VDE 0620 Part 1.  
With claw and screw fixing.

Version	Art. no.	PU	PG	Mat.	Info
white	<b>271327</b>	5/20	1.5		



### SCHUKO triple socket-outlet

**16 A, AC 250 V, DIN 49440**

With plug-in terminals as connecting terminals in accordance with VDE 0620 Part 1.

- Note:** For cavity wall installation: Use special box, art. no. 9062 from the Kaiser company in Schalksmühle, Germany.

**Contents:** Complete device with double mounting box and fixing screws.

Version	Art. no.	PU	PG	Mat.	Info
white	<b>231224</b>	5/30	1	DP	
polar white	<b>231218</b>	5/30	1	DP	



### Double mounting box

**Plastic**

Replaces two size 60 mounting boxes.  
Box is suitable for all conventional twin combinations.

Double mounting box for surface installation of PLANTEC with 8/18 function keys and display in solid walls.

Version	Art. no.	PU	PG	Mat.	Info
	<b>528668</b>	1/30	1		



### Impact-resistant SCHUKO socket-outlet, flush-mounted

**16 A, AC 250 V, DIN 49440**

Full, gently-curved top cover (100 x 100 mm).  
With screw terminals as connecting terminals in accordance with VDE 0620 Part 1.  
The dowel fixing provides protection in case the cable is pulled with excessive force.

- Contents:** Complete device.

Version	Art. no.	PU	PG	Mat.	Info
white	<b>270727</b>	5/15	1		
polar white	<b>270719</b>	5/15	1		



### SCHUKO e.l.c.b.-protected socket-outlet with hinged lid and improved protection against accidental contact

Integrated, improved protection against accidental contact in accordance with VDE 0620 Part 1 (replaces the previous designation "child protection").

Constructed in accordance with VDE 0664 (EN 61008). For the improvement of safety in existing installations according to VDE 0100 Part 410. Output to connect further loads.

For integration into a size 60 mounting box.

The e.l.c.b.-protected socket-outlet can be retrofitted for additional protection against damp using the gasket set.

**Voltage:** AC 230 V

**Fault current:** 30 mA

**Max. current:** 16 A

**Short-circuit withstand capability:** 3000 A

**Type of protection:** IP 20

- Accessories:** Gasket set, art. no. 232990.

- Contents:** Complete device.

Version	Art. no.	PU	PG	Mat.	Info
polar white	<b>232999</b>	1/24	8.1	TP	



### Gasket set

The e.l.c.b.-protected socket-outlet can be retrofitted for additional protection against damp using the gasket set.

- To be completed with:** SCHUKO e.l.c.b.-protected socket-outlet with hinged lid, art. no. 232999.

Version	Art. no.	PU	PG	Mat.	Info
Gasket set	<b>232990</b>	1/70	1	TP	



## SCHUKO triple table-type socket-outlet

16 A, AC 250 V, DIN 49440

Can be unscrewed; with shatter-proof cap.  
Without incoming cable, with strain relief.  
With screw terminals as connecting terminals in accordance with VDE 0620 Part 1.

Version	Art. no.	PU	PG	Mat.	Info
white	276392	10/40	3		
dark brazil	276390	10/40	3		

### SCHUKO plugs and sockets



## SCHUKO plug

16 A, AC 250 V, DIN 49441

Small, shatter-proof quality plug with recessed grips.

Version	Art. no.	PU	PG	Mat.	Info
white	122427	30/240	3.1		
grey	122463	30/180	3.1		
dark brazil	122415	30/180	3.1		



## SCHUKO plug (DE, FR, BE)

16 A, AC 250 V, DIN 49441, CEE 7 Standard Sheet 7

With German and French earthing contact.  
Small, shatter-proof quality plug with recessed grips.

Version	Art. no.	PU	PG	Mat.	Info
grey	123363	30/180	3.1		



## SCHUKO connector

16 A, AC 250 V, DIN 49440

Small, easy-to-grip connector with shatter-proof housing.

Version	Art. no.	PU	PG	Mat.	Info
white	172427	15/120	3.1		
grey	172463	15/90	3.1		
dark brazil	172415	15/90	3.1		



## SCHUKO plug with lateral insertion

16 A, AC 250 V, DIN 49441

With shatter-proof handle and lateral insertion.

Version	Art. no.	PU	PG	Mat.	Info
mocha/bronze	120842	10/80	3.1		



## Shatter-proof SCHUKO plug

16 A, AC 250 V, DIN 49441

With lateral insertion and one-piece, shatter-proof housing.

Version	Art. no.	PU	PG	Mat.	Info
white	120927	25/200	3.1		
dark brazil	120915	25/150	3.1		



## Shock-proof SCHUKO plug with bend protection sleeve

16 A, AC 250 V, DIN 49441

With lateral insertion, bend protection sleeve and one-piece, shatter-proof housing.

Version	Art. no.	PU	PG	Mat.	Info
grey	120963	20/120	3.1		



## SCHUKO angled plug with toggle switch

16 A, AC 250 V, DIN 49441

With 2-pole toggle switch.  
Shatter-proof lid.

Version	Art. no.	PU	PG	Mat.	Info
white	128427	15/90	3		



## SCHUKO angled plug with toggle switch and control lamp

16 A, AC 250 V, DIN 49441

With 2-pole toggle switch.  
Shatter-proof lid, control light.

Version	Art. no.	PU	PG	Mat.	Info
white	128474	15/90	3		



## SCHUKO angled plug with toggle switch (DE, FR, BE)

16 A, AC 250 V, DIN 49441, CEE 7 Standard Sheet 7

With German and French earthing contact.  
With 2-pole toggle switch.  
Shatter-proof lid.

Version	Art. no.	PU	PG	Mat.	Info
white	128527	15/90	3		



## SCHUKO angled plug with toggle switch, control lamp (DE, FR, BE)

16 A, AC 250 V, DIN 49441, CEE 7 Standard Sheet 7

With German and French/Belgian earthing contact.  
With 2-pole toggle switch.  
Shock-proof lid, control light.

Version	Art. no.	PU	PG	Mat.	Info
white	128574	15/90	3		



## PVC SCHUKO plug

16 A, AC 250 V, DIN 49441

Splash-proof plug.  
Large version, with bend protection sleeve.



Version	Art. no.	PU	PG	Mat.	Info
white	125462	15/90	3.1		
grey	125463	15/120	3.1		



## PVC SCHUKO plug (DE, FR, BE)

16 A, AC 250 V, DIN 49441, CEE 7 Standard Sheet 7

With German and French/Belgian earthing contact.  
Splash-proof.  
Large design, with bend protection sleeve.



Version	Art. no.	PU	PG	Mat.	Info
grey	123463	15/90	3.1		



## PVC SCHUKO connector

16 A, AC 250 V, DIN 49440

Large version, with bend protection sleeve.

Version	Art. no.	PU	PG	Mat.	Info
white	173762	10/60	3.1		
grey	173763	10/60	3.1		



## SCHUKO triple suspended connector

16 A, AC 250 V, DIN 49440

Made from chipped linen material.  
Shatter-proof, with hanger.

Version	Art. no.	PU	PG	Mat.	Info
black	179625	1/30	3		



## SCHUKO triple connector

16 A, AC 250 V, DIN 49440

Made from pressed material.

Version	Art. no.	PU	PG	Mat.	Info
white	179627	1/30	3		



## Mobile garden socket-outlet without incoming cable

16 A, AC 250 V, DIN 49440

Splash-proof SCHUKO double socket-outlet.  
An ideal current distributor for garden parties, for mowing the lawn and so on.  
Stable, weather-resistant plastic bracket.  
With screw terminals as connecting terminals in accordance with VDE 0620 Part 1.



Version	Art. no.	PU	PG	Mat.	Info
black/grey	599893	1/3	3.1		



## Mobile garden socket-outlet with 5 m incoming cable

16 A, AC 250 V, DIN 49440

Splash-proof SCHUKO double socket-outlet.  
An ideal power distribution system for garden parties, cutting the lawn etc. With 5 m incoming cable 3x1 mm<sup>2</sup> H 05 RN-F and integral rubber SCHUKO plug. Stable, weather-resistant plastic bracket.



With screw terminals as connecting terminals in accordance with VDE 0620 Part 1.

Version	Art. no.	PU	PG	Mat.	Info
black/grey	599894	1/3	3.1		

## PERILEX plugs and connectors

- For many applications there is no time limit on the use of PERILEX.
- Blocks of flats, business premises, hotels, laboratories, large kitchens and similar plants can even today still be safely installed to modern standards using PERILEX.
- Splash-proof, similar to IP 44.



### PERILEX plug

16 A, AC 400 V, DIN 49446


Version	Art. no.	PU	PG	Mat.	Info
white	134027	10/50	5		



### PERILEX connector

16 A, AC 400 V, DIN 49445

Version	Art. no.	PU	PG	Mat.	Info
white	183027	10/60	5		



### PERILEX angled plug

16 A, AC 400 V, DIN 49446

Version	Art. no.	PU	PG	Mat.	Info
white	130027	10/60	5		



### PERILEX socket-outlet, flush-mounted

16 A, AC 400 V, DIN 49445

With retaining ring.  
For integration into a size 70 mounting box.

Version	Art. no.	PU	PG	Mat.	Info
white	250427	10/30	5		



### PERILEX socket-outlet, flush-mounted, with hinged lid

16 A, AC 400 V, DIN 49445

Version	Art. no.	PU	PG	Mat.	Info
white	255027	10/50	5		



### All-rubber PERILEX plug

16 A, AC 400 V, DIN 49446

Splash-proof. With membrane seal. Robust plug with rubber lip. Corrosion-resistant and shatter-proof.

IP44

Version	Art. no.	PU	PG	Mat.	Info
black	134251	10/30	5		



### All-rubber PERILEX connector

16 A, AC 400 V, DIN 49445

Robust connector.  
Corrosion-resistant and shatter-proof.  
With membrane seal.

Version	Art. no.	PU	PG	Mat.	Info
black	183251	10/30	5		



### PVC PERILEX plug

16 A, AC 400 V, DIN 49446

Shatter-proof contact bracket insert made from high-quality, electric insulation material. With membrane seal.



Version	Art. no.	PU	PG	Mat.	Info
grey	134163	10/30	5		



### PVC PERILEX connector

16 A, AC 400 V, DIN 49445

Shatter-proof contact bracket insert made from high-quality, electric insulation material. With membrane seal.

Version	Art. no.	PU	PG	Mat.	Info
grey	183163	10/30	5		



### PERILEX socket-outlet, flush-mounted, with hinged lid

16 A, AC 400 V, DIN 49445

Splash-proof.  
With shatter-proof hinged lid.



**Contents:** With mounting box for large plaster adjustment.

Version	Art. no.	PU	PG	Mat.	Info
white	253227	10/30	5		



## PERILEX socket-outlet, surface-mounted, with hinged lid

16 A, AC 400 V, DIN 49445

Splash-proof.  
With shatter-proof hinged lid.



Version	Art. no.	PU	PG	Mat.	Info
grey	258329	10/30	5		



## Slide with gland

For cables and leads.

- ▣ **To be completed with:** PERILEX socket-outlet, surface-mounted, with hinged lid, art. no. 258329.

Version	Art. no.	PU	PG	Mat.	Info
grey	258309	10/300	5		



## Slide without gland

For cables and leads.

- ▣ **To be completed with:** PERILEX socket-outlet, surface-mounted, with hinged lid, art. no. 258329.

Version	Art. no.	PU	PG	Mat.	Info
grey	258311	10/400	5		



## PERILEX angled plug, 25 A

25 A, AC 400 V, DIN 49448

Made from pressed material.

Version	Art. no.	PU	PG	Mat.	Info
white	130527	10/20	5		



## PERILEX socket-outlet, flush-mounted, 25 A

25 A, AC 400 V, DIN 49447

With retaining ring.

- ▣ **Accessories:** Insulating mounting box, art. no. 528304.

Version	Art. no.	PU	PG	Mat.	Info
white	250327	1/20	5		



## Insulating mounting box

- ▣ **To be completed with:** PERILEX socket-outlet, flush-mounted, 25 A, art. no. 250327.

Version	Art. no.	PU	PG	Mat.	Info
black	528304	1/30	5		

## HNA plugs and connectors

- The HNA plugs and connectors are indispensable in special circuits to differentiate between normal circuits.
- HNA plugs and connectors have proved particularly suitable for powering EDP systems via a special circuit.



## HNA plug

10 A, 250 V, C 220 DIN 89321

Version	Art. no.	PU	PG	Mat.	Info
grey	105129	10/80	7		



## HNA angled plug

10 A, 250 V, C 220 DIN 89321

Splash-proof, comparable to IP 44



Version	Art. no.	PU	PG	Mat.	Info
white	105327	10/100	7		



## HNA socket-outlet, flush-mounted

10 A, 250 V, B 220 DIN 89321

With full cover plate.  
For socket-outlets where it is essential that they are not interchanged.

Version	Art. no.	PU	PG	Mat.	Info
grey	200129	10/40	7		



## HNA socket-outlet insert

10 A, 250 V, B 220 DIN 89321

For System Basis.  
For socket-outlets where it is essential that they are not interchanged.

- ▣ **Adapters:** Can be integrated into System Design using the adapter, art. no. 5180..., and into the OCTOCOLOR range using the adapter, 5170... Can be installed in damp rooms or outdoors using the protective cover with gasket, art. no. 5172...

Version	Art. no.	PU	PG	Mat.	Info
white	204074	10/40	7	DP	
polar white	204019	10/40	7	DP	



## HNA socket-outlet insert

10 A, 250 V, B 220 DIN 89321

For System M.  
For socket-outlets where it is essential that they are not interchanged.

Version	Art. no.	PU	PG	Mat.	Info
white	204144	10/40	7	TP	
polar white	204119	10/40	7	TP	



## HNA socket-outlet, surface-mounted

10 A, 250 V~, A 220 DIN 89321

For socket-outlets where it is essential that they are not interchanged.

**Contents:** With cable and mini-trunking entry (15 mm).

Version	Art. no.	PU	PG	Mat.	Info
white	205444	10/70	7		



## HNA socket-outlet, surface-mounted

10 A, 250 V~, A 220 DIN 89321

Splash-proof.

For socket-outlets where it is essential that they are not interchanged.



Version	Art. no.	PU	PG	Mat.	Info
grey	208429	10/50	7		

### CEE 17 plugs and connectors

- Shatter-proof housing.
- Splash-proof, comparable to IP 44.



## CEE 17 socket-outlet, surface-mounted

380 to 415 V, 16 A, 6 h

3 P + N +  $\perp$ , in line with DIN 49462  
With screw terminals.  
Suitable for surface mounting.



**Contents:** 2 cable entries with PVC nipple.

Version	Art. no.	PU	PG	Mat.	Info
light grey	260629	2/24	5		



## SCHUKO socket-outlet, surface-mounted

16 A, AC 250 V, DIN 49440

With screw terminals as connecting terminals in accordance with VDE 0620 Part 1.



**Contents:** 2 cable entries with PVC nipple.

Version	Art. no.	PU	PG	Mat.	Info
light grey	260691	2/24	5		



## Workshop combination CEE 7/17, 6 h, surface-mounted

SCHUKO socket-outlet: 16 A, AC 250 V, DIN 49440.

Combined with CEE 17 socket-outlet 3 P + N +  $\perp$ , to DIN 49462: 380 to 415 V, 16 A, 6 h.

With T10 A micro-fuse in the SCHUKO socket-outlet.

Version	Art. no.	PU	PG	Mat.	Info
light grey	266729	1/12	5		



## SCHUKO double socket-outlet, surface-mounted

16 A, AC 250 V, DIN 49440

With screw terminals as connecting terminals in accordance with VDE 0620 Part 1.

**Contents:** 4 cable entries with PVC nipple.

Version	Art. no.	PU	PG	Mat.	Info
light grey	229929	1/12	5		



## CEE 17 socket-outlet, flush-mounted

380 to 415 V, 16 A, 6 h

3 P + N +  $\perp$ , in line with DIN 49462  
With screw terminals.

**Contents:** Mounting box, 4 fixing screws.

Version	Art. no.	PU	PG	Mat.	Info
white	265644	1/16	5		



## CEE 17 socket-outlet, built-in version

380 to 415 V, 16 A, 6 h

3 P + N +  $\perp$ , in line with DIN 49462  
For cavity walls, cast concrete, trunking and machines.

Fixing screw with 67 mm clearance.  
With screw terminals.

**Contents:** Without mounting box.

Version	Art. no.	PU	PG	Mat.	Info
white	265627	2/24	5		

**CEE 17 angled plug****380 to 415 V, 16 A, 6 h**3 P + N +  $\perp$ , in line with DIN 49462

Angled cable outlet so that the plug fits all CEE 17 socket-outlets.

Version	Art. no.	PU	PG	Mat.	Info
white	<b>136644</b>	2/24	5		